



## Features

- Pb free product—RoHS compliant
- Low power consumption, High efficiency
- Reliable and rugged
- Long life – solid state reliability
- Fast response time
- High photo sensitivity

## Package Dimension

### Notes:

1. All dimensions are in millimeters.
- 2.



## Electrical Optical Characteristics at Ta=25

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
	0.5	780	---	1100	nm	---
	P	---	940	---	nm	---
Collector-Emitter Breakdown Voltage	$BV_{CEO}$	30	---	---	V	$I_C=0.1mA$ $E_e=0mW/cm^2$
Emitter-Collector Breakdown Voltage	$BV_{ECO}$	5	---	---	V	$I_E=0.1mA$ $E_e=0mW/cm^2$
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	---	---	0.4	V	$I_C=0.1mA$ $E_e=1mW/cm^2$
						$V_{CE}=5V$ $I_C=1mA$ $R_L=1000$
Viewing Angle	1/2	---	50	---	Deg.	---
Collector Dark Current	$I_{CEO}$	---	---	100	nA	$V_{CE}=10V$ $E_e=0mW/cm^2$
On State Collector Current	$I_{C(ON)}$	1.0	---	---	mA	$V_{CE}=5V$ $E_e=1mW/cm^2$

### Note:

1/2 is the off-axis angle at which the  $I_{C(ON)}$  is half the axial  $I_{C(ON)}$ .

2. The  $I_{C(ON)}$  guarantee should be added  $\pm 15\%$  tolerance.







### Suggest IR Reflow Condition For Lead Free

